



KP 905 E

TECHNICAL DATA SHEET

Introduction

- Excellent sanding by the precisely coated aluminum oxide grit.
- Sanding options by sanding machine.
- High finishing level for perfect smooth surface.



Backing Material	Antistatic "E" weight paper
Bonding	Double resin
Mineral Type	Aluminum Oxide
Coating State	Semi-open coat
Manufacturing Width	1400mm

Available Grits

24	36	40	50	60	80	100	120	150	180	220	240
		●	△	●	●	●	●	●	●	●	
280	320	360	400	500	600	800	1000	1200	1500	2000	2500

◀ Rough (Grinding)

Finishing (Polishing) ▶

- Introductory Remarks ● : Standard Grit △ : Non Standard Grit (Available under request with a MOQ)

Application

- > Dry use
- > Rough sanding and fine sanding of wood, paints and fillers

Field

- > Wood

Form

- > Rolls
- > Belts

Usage



Head Office:

Via Delle Groane, 27/E 20024 Garbagnate M. -Mi- Italy

E-mail: itas.it@itasabrasivi.com

Website: www.itasabrasivi.com

I.T.A.S. ABRASIVES CO., LTD.

Yunxin Avenue, Yungang Road,

414009, Yueyang City, Hunan, China

Tel. +86 0730 3072778 / +86 0730 3072998

E-mail: itas.cn@itasabrasivi.com